

3M™ Supplied Air

Visor System - AL4P



The 3M Supplied Air Visor System – AL4P features an air regulating valve and acetate nod down painting shield with foam face seal. An optional Y-piece take off (shown) may be fitted allowing the use of one airline hose to provide air for respiratory protection and spray gun.

Features

- Acetate visor with Medium Impact visor rating (AS1337)
- Meets performance requirements of AS/NZS 1716
- Provides a Protection Factor of 100+ against particulates and gases/vapours AS/NZS 1715
- Silicone free headpiece
- Airline couplings are CEJN fittings

Requirements

- Pressure requirement at regulator

Hose Length	PSI
7.5m	25-30
15m	30-35
30m	35-40

- Minimum Manufacturer's Design Flow 170 l/min (6.6 cfm)
- Free air volume user variable between 170 – 425 l/min (6 – 15 cfm)

	Product Code	3M Order Code
Supplied Air Visor System - AL4P	AL4P	AT019167322

Spare Parts

	Product Code	3M Order Code
Foam Faceseal	2002346-0P	52000017906
Visor Acetate	310-03-74P	52000017864

Optional Accessories

	Length	Product Code	3M Order Code
Air Line Breathing Hoses with CEJN Fittings – Approved to AS 1716	7.5m	901-00-56	AT019165714
	10m	901-00-55	AT019165706
	15m	01-00-54	AT019165698
Breathing Air Panel with CEJN Fittings		901-00-47	AT019184335
Y-piece takeoff fitting allowing connection to HVLP paint spray guns (max. 2 bar supply pressure)		312-00-87P	52000004334



How to contact us

3M Australia Pty Ltd
Phone 136 136

3M Australia Pty Ltd Customer Service
Phone 1300 363 565
Fax 1800 656 222

3M TechAssist Hotline
Phone 1800 024 464

World Wide Web
www.3m.com/au/ohs

© Copyright 3M Australia Pty. Limited 2006

Neither whole or part of this publication may be reproduced without prior permission.



Protecting your way of life.

3M Innovation