

RAFTER-MOUNTED ROOF ANCHOR FOR TILE ROOF

STANDARD
EN 795 : 2012
type A



USE (see technical manual)

VECTASAFE® rafter-mounted roof anchor for tile roof is a multi-directional energy absorber anchor point, which is intended for the safety of one user maximum.

It enables workers equipped with PPE (Personal Protective Equipment) to secure their movements during work at height, maintenance, and cleaning works. The anchor plate has been especially designed for use on timber rafters under tile roof.

TECHNICAL CHARACTERISTICS

- **Material:** 316 stainless steel
- **Weight:** 0.634 kg
- **Resistance:** 1800 DaN
- 360° multi-directional
- **Compliance with standard:** EN 795: 2012 type A
- **Certifications:** n°52872476_10

ADVANTAGES OF THE PRODUCT

- > Quick installation
- > Discrete design, only the anchor ring is visible.
- > The highly flexible design ensures installation on the majority of tiled roofs.

INSTALLATION RECOMMENDATIONS (see technical manual)

Fixing:

- 10 sleeper screws TH Ø5 mm, 50 mm minimum implantation inox (DIN 571)
- Minimum dimensions of structure: width 50 mm x 90 mm, structural solid wood, minimum strength class C24.



RAFTER-MOUNTED ROOF ANCHOR FOR TILE ROOF

DIMENSIONS (in mm)

