

Light

DANY OB

Trendy clog with a playful touch

| | |
|-----------------|------------------------------------------------------|
| Upper | Synthetic Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Outsole | EVA/Rubber |
| Safety standard | OB / ESD, A, E, SRC |
| Size range | EU 35-47 / UK 3.0-12.0 US 3.0-13.0 / CM 23.0-31.0 |
| Sample weight | 0.235 kg |
| Norms | EN ISO 20347:2012 ASTM F2892:2018 |



LBL



BLK



FUC



MUG



MUL




WHT




Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.




Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.

Industries:

Catering, Cleaning, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|-------------------------------------------|--------------|--------|--------------|
| Upper | Synthetic Leather | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 3.3 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 28 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 43.7 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 350 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | EVA/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 129 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.38 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.36 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.17 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.24 | ≥ 0.18 |
| | Antistatic value | MegaOhm | NA | 0.1 - 1000 |
| | ESD value | MegaOhm | 80 | 0.1 - 100 |
| | Heel energy absorption | J | 26 | ≥ 20 |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com