



EN ISO 20345:2022



RESOLUTE TENACE BOA 45524-00L

S7S FO HI CI SC HRO SR
Size: 36-48
Weight: 850 gr.

Fit: 11

Working Environment:
 Building, Farming and Gardening,
 Mountains, Wood-metal
 carpentry


FEATURES

UPPER

 Full Grain leather Hydro 1,8-2,0 mm
 No ladder H.T. Fabric
 Reflex insert

LINING

 GenuineWool Polar
 GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation 2.0

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Half-knee Boot

SOLE

**PU-RUBBER VIBRAM ECOSTEP
PRO-HRO-SR**

 Sole with anti-wear scaff cap.
 Outsole in VIBRAM RECYCLED
 (≥30%) rubber, resistant to 300° C
 by contact (HRO), to acids and oils.
 Design with self-cleaning outsole,
 with SR Antislip standard.

Boa® lace length

L+1 - 100cm Top - 85cm Bottom

TECHNOLOGIES

Removable Insole


 The ideal insole in recycled material
 for footwear with "CI" cold protection.
 The presence of felt with an
 "aluminized" film for bottom
 insulation keeps the foot dry and
 warm.


Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

fibercap sxt

 Composite toecap with fiberglass.
 Resistant to over 200J. Non metal
 perforation resistant insert to over
 1100 N with a 3.0 mm truncated cone
 nail. Protection over the entire sole of
 the foot. Flexible and comfortable


Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.


Torsional stability



STABIL • ACTIVE

 Support made of rigid plastic
 material. It supports the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


Electrical features



Wire Electricity Discharge

 Strip with 4 filaments of carbon fiber,
 ensuring proven anti-static properties
 of the footwear over time.


Other


 PROGRESSIVE CUSHIONING
 AND ADAPTIVE STABILITY

 D3O materials are made using a
 combination of advanced polymer
 chemistry and cutting-edge science.
 It absorbs and dissipates energy
 during and impact, with superior
 stability, cushioning and anti-fatigue
 effect.


PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

BASIC
 CERAMIC WITH
 NALS

 FORWARD
 HEEL SLIP
 ≥ 0.31
 BACKWARD
 FOREPART SLIP
 ≥ 0.36

0,45
0,47

SR
 CERAMIC WITH
 GLYCERINE

 FORWARD
 HEEL SLIP
 ≥ 0.19
 BACKWARD
 FOREPART SLIP
 ≥ 0.22

0,28
0,25
