


Model	Line	Standard
CAPRI	URBAN	EN ISO 20345:2011
Article	Protection	Availability in stock
82149-11L	S3 SRC	AVAILABLE 



Preview	Sole	PU Dual-Density SRC passed
---------	------	----------------------------



Two-component PU outsole with tread designed mainly for indoor use. Self-cleaning design and highly non-slip grip. SRC Antislip standard.

Removable Insole



The upper layer in contact with the foot is made of a highly resistant netting to ensure exceptional absorption of dampness. A self-forming antibacterial foam layer ensures comfort and correct support of the foot.

Protection Elements



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.

Type	Low Shoe
Upper	Full Grain Drummed leather Hydrotech Soft Full Grain Leather
Lining	3D Air circulation 320 gr.
Antislip Lining	DUALMICRO
Removable Insole	Flyfit
Sole	PU Dual-Density SRC passed
Toe Cap	C.T.C. - Composite Toe Cap
Anti-Perforation	ZERO (k) ANTIPERFORATION
Size	36-48
Weight gr.	580

Working Environment

Multipurpose, Wood-metal carpentry, Logistics and Light Industry, Componentistica e Automotive

SRC

SRC (SRA+SRB)		
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.47
	HEEL (1000N/4000N) ≥ 0.28	0.43
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.21
	HEEL (1000N/4000N) ≥ 0.13	0.16

Antistatic



Wire Electricity Discharge
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.

Plus



Double non-slip layer of microfibre, resistant up to 200,000. Makes the footwear more comfortable, blocking the foot during use.

Plus



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Features



Symbols

