

TECHNICAL DATA SHEET

PBH06

TDS09



Checkmate Vantage Rescue Harness

The PBH06 is designed to support the body and distribute the forces to prevent serious injury and keep the worker in a safe position ready for rescue in the event of a fall. The extended rear D provides secondary connection for rescue purposes only.

VANTAGE

Safety by Design



Rescue Strop

The rear of the PBH 6 incorporates an integral rescue lanyard sewn to the adjustable rear "D" connection.



Fall Arrest Indicator

Fall arrest indicating tabs allow the user to easily and confidently determine if the harness has been subjected to fall forces.



Trapezoidal Buckles

Angled buckles ensure the harness webbing follows the contours of the body for a more secure and comfortable fit.



Reinforced Webbing

Potential stress points are reinforced for an extra level of safety and durability.



Contrast Stitching

Grey contrast stitching is used so that on inspection, prior to donning, the user can determine the integrity of the harness.

ordering information

Part No.	Description	Weight
▼ PBH06	Two point pro body harness with rescue strop (S,M,L,XL,XXL)	1.4kg(M)
Accessories		
▼ TL4.5	Tool lanyard	<1kg
▼ PPEB-33	Parking loop	<1kg
▼ PPEB-23	Shoulder yoke	<1kg



TL4.5
Tool Lanyard
(Optional Accessory)



PPEB-33
Parking Loop
(Optional Accessory)



PPEB-23
Shoulder Yoke
(Optional Accessory)



Rear "D"

Rescue Strop

Contrast Stitching

Front "D"

Back Support & Label Pouch

Two Colour Body to Leg Webbing



scope of use

Certified fall arrest points are clearly marked with an A, the rear "D" should always be your primary anchorage, although front "D" connection is permitted for fall arrest but is primarily for work positioning. The extender D is for rescue only. The PBH06 must be used in conjunction with an energy absorber or load limiting device. Maximum impact force 6kN. When used for fall arrest a pre-determined rescue plan must be a part of your safe system of work. Recommended anchorage strength 12kN.

specifications

- ▼ **Anchorage**
Rear D dorsal attachment point
Sternum attachment point
- ▼ **Fittings**
Carbon Steel, Black Powder Coated
- ▼ **Webbing**
Polyester Webbing, Water Repellent & UV Resistant
- ▼ **UserWeight**
150kg Maximum [Including tools and equipment]

standards

- ▼ EN361, EN 1497 : 2007



CHECKUSOUT

www.checkmateuk.com

