# **WG-787** Dexcut<sup>™</sup>



Cut-resistance

**PROTECTION** 

# NORMS









### **DOCUMENTS**

You can also download on our website:

- Product technical sheet
- EU certificate
- Declaration of Conformity
- Food contact information
- User instructions

WG-787 Dexcut™ is a single nitrile coated glove, in a 13-gauge HPPE, mineral fibre and spandex liner providing cut resistance (ISO 13997 grade D), while offering unrivalled flexibility and breathability. WG-787 Dexcut™ is made from Tsunooga™ high performance polyethylene fibres to provide superior cut resistance, while maintaining excellent flexibility and comfort, in dry and oily applications.

# **APPLICATIONS**

- Automotive
- Metallurgy
- Steel industry
- Recycling
- Industrial maintenance
- Sorting
- Assembly
- Installation and handling of very sharp parts or objects

## **INFORMATION**

# Coating

Nitrile single dip, Palm fit

Spandex, Tsunooga and Technical Fiber, 12 pairs / polybag

# Gauge

13

# **Packaging**

144 pairs / box

### DIMENSIONS Tolerance ±5%

SIZE	6 / XS	7 / S	8 / M	9 / L	10 / XL	11 / XXL
Hem Color		Light purple	Green	Cream	Light blue	Black
Overall Length (mm)		240	255	264	275	285
Palm width (mm)		90	95	97	103	107
Length of middle finger (mm)		75	78	82	88	95
Thickness (µm)		1400	1400	1400	1400	1400
Weight (g/pair)		55	60	67.7	73.6	76.9
Liner Weight (g/pair)		39.1	42.6	48.1	52.3	54.6
Coating Weight (g/pair)		15.9	17.4	19.6	21.3	22.3

# **CARTON INFORMATION**

Carton Volume (m,m³)	Length 0.530 × Width 0.315 × Height 0.280 : Volume 0.047 (m³)							
Carton Net Weight (kg)		8.5	9	9.9	10.7	11.6		
Carton Gross Weight (kg)		9.5	10	10.9	11.7	12.6		

