

SPLINE SUMP TYPE PW



	Max. no. of 200 litre drums	Dimensions in mm (l x w x h)	Retention capacity in l	Load capacity in kg	Weight painted / galv. in kg
PW 200-2	2	1200 x 800 x 360	242	600	64 / 69
PW 200-4	4	1200 x 1200 x 285	257	1200	77 / 83
PW 400-4	4	1200 x 1200 x 410	435	1200	91 / 98

Storage of max. 4 x 200 litre drums or 200 l drums in combination with 60 litre drums

- construction made of 3 mm steel sheet
- drums stand on splines
- 100 mm ground leeway
- can be stacked



- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4

Finish:	RAL 2000	RAL 3000	RAL 5012	RAL 6011	RAL 7005	hot-dip galvanized
---------	----------	----------	----------	----------	----------	--------------------

SUMP TRAYS TYPE ECO-S



ECO-S 4/200 - shipping unit



ECO-S 2/200

	Max. no. of 200 litre drums	Dimensions in mm (l x w x h)	Retention capacity in l	Weight galvanized in kg
ECO-S 2/200	2	1200 x 800 x 360	232	48
ECO-S 4/200	4	1200 x 1200 x 280	240	70
ECO-S 4/400	4	1200 x 1200 x 430	440	80

A conical construction optimized for logistics; for the storage of max. 4 x 200 l drums or 200 l drums in combination with 60 litre drums and/or canisters and small cans

- construction made of 2 mm steel sheet
- 100 mm ground leeway
- galvanized grid (load capacity 650 kg/m²)
- conical construction
- can be stacked one inside another (grid separate)
- for use with a pallet truck or forklift truck
- shipping unit: 15 pieces per Euro pallet

- every unit tested for leakage
- flammable liquids, GHS categories 1 - 3
- hazardous to aquatic environment, GHS categories 1 - 4

Finish:	hot-dip galvanized
---------	--------------------